interstuhl

Technical data sheet 16V2

Specification Office swivel chair low, seat and back upholstered

Dimensions in mm	Backrest:	H:	425
	Seat:	H:	400-525
		W:	500
		D:	520
	Total:	H:	1045
		W (no ArmR):	545
		W (ArmR):	600
		D:	590
Packaging data	Weight:	kg	19
	Volume:	m³	0,51



Basic equipment		Benefit
Backrest	Back low, upholstered, 30 mm foam.	Great seating comfort due to the ergonomically designed backrest.
Jpholstery	Seat upholstered. Breath actively moulding foam, CFC - CHC - free (segregated foam). Seat 35 mm foam + 10 mm cotton.	Paddings are unglued, ensuring optimal air movement, breathable.
<i>N</i> echanism	Smart Motion Technology, lockable in 4 positions. Opening angle between seat and back up to 110°.	The perfectly kinematic movement of the Smart Motion Technology encourages the user to change seating position frequently; in addition, the active seat inclination supports an ergonomic position especially when working at the desk.
Seat height adjustment	Seat height adjustment infinitely variable from 400 - 525 mm. Self-supporting safety gas spring.	Even people outside the DIN range (i.e. taller than 192 cm and smaller than 151cm) will sit in the most ergonomic way.
Seat depth adjustment	Sliding seat for individual seat depth adjustment. Can be adjusted by 70 mm.	The real support area for the thighs of taller people will be enlarged.
Seat inclination	Flexible adaption to users movements forward +2° and backward -5°, lockable.	The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column.
Veight Adjustment	From 45 - 130kg, adjustable per ratchet element in 10 levels.	Individual adjustment of the backrest and the back pressure to the weight and height of the user.
Castors	Hard castors, load-dependent braked, for soft floors (according to DIN EN 12529).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Aluminium base, black.	Very high stability, long service life.
<i>f</i> laterials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for having tested safety, tested for contaminants and ergonomics.	High quality product and great comfort.

interstuhl

Technical data sheet 16V2

Specification Office swivel chair low, seat and back upholstered

Narranty and return		10 years warran recycling guaran	ty. Complete return and itee.	Exchange of parts free of charge within the guaranteed period.
		(EMAS), Environ DIN EN ISO 140 Management Sy EcoVadis Gold.	imental Management System 101:2015, Health and Safety stem DIN EN ISO 45001:2018, Commitment to sustainability. Iue Angel, Bifma e3 level Platin.	
Certification			ment system DIN EN ISO ulation (EC) no. 1221/2009	High quality product.
	Volume:	m³	0,51	
Packaging data	Weight:	kg	19	
		D.		
		W (ArmR): D:	600 590	
		W (no ArmR):	545	
	i otal:	H:	1045	
	Total:	D:	520	
		W:	500	
	Seat:	H:	400-525	
Dimensions in mm	Backrest:	H:	425	

Disassembly instructions are available upon request for any interstuhl product

interstuhl

Technical data sheet 16V2

Specification Office swivel chair low, seat and back upholstered

Dimensions in mm	Backrest:	H:	425
	Seat:	H:	400-525
		W:	500
		D:	520
	Total:	H:	1045
		W (no ArmR):	545
		W (ArmR):	600
		D:	590
Packaging data	Weight:	kg	19
	Volume:	m³	0,51



Options		Benefit
Castors	Soft castors, load-dependent braked, for hard floors (acc. to DIN EN 12529) or glides(soft/hard).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Aluminium base, anthracite, chromed or aluminium polished.	Very high stability, longevity.
Mechanical sprung column	Also in the lowest seating position.	Damping of an excessive vertical impact, so that the spine will be preserved.
umbar support	Depth- (26 mm) and height adjustable (64 mm).	The lumbar support is depth adjustable and can be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible.
Armrests	Aluminium ring arm rests with or witouth leather pads, polished or chromed. 3D Auto Flow arm rests, adj. in height (100 mm) & width (460 - 530 mm), soft 3D T-arm rests, adj. in height (100 mm) & width (450 - 520 mm), depth (60 mm), soft.	The armrests relieve the neck and shoulder muscles.
Material	Several fabric collections are available in different colours.	During the design of the chair several colours and upholstery materials are available.

Disassembly instructions are available upon request for any interstuhl product